



DLS FLATBOX[®]

Latest news

Flatbox M series

These are the latest members in the Flatbox family developed to extend the range of On-wall speakers. There are some unique features to point out that gives them an overwhelming sound.

- 6,5" Kevlar cone mid bass drivers
- 30 mm waveguide tweeters
- Time alignment
- Bi-wire

M-One

Speaker facts M-One

Type :	2-way bass reflex
Impedance :	4 ohms
Sensitivity :	91 dB/1m, 1W
Recommended amplifier :	50 - 150 Watts
Frequency response (-6 dB) :	45 Hz - 30 kHz
Woofer/mid :	6,5", kevlar cone
Tweeter :	30 mm Waveguide
Weight :	8,5 kg per speaker
Extra:	Wall bracket included Bi-wire
Finish:	White satin or piano black Both white and black front grilles are included

Dimensions:

Height:	600 mm (23,6")
Width:	280 mm (11,02")
Depth:	111 mm (4,37") incl. wall bracket

M-Two

Speaker facts M-Two

Type :	2.5-way bass reflex
Impedance :	4 ohm
Sensitivity :	92 dB/1m, 1W
Recommended amplifier :	50 - 250 Watt
Frequency response (-6 dB) :	40 Hz - 30 kHz
Woofer :	6,5", aluminum cone
Woofer / mid :	6,5", kevlar cone
Tweeter :	30 mm waveguide
Weight :	16,9 kg per speaker
Extra:	Wall bracket included Bi-wire
Finish:	White satin or piano black Both white and black front grilles are included

Dimensions:

Height:	1050 mm (41,3")
Width:	320 mm (12,6")
Depth:	111 mm (4,37") incl. wall bracket

